

Nexio Infrared Touch Screen

# NIB Series



## Applications

Digital signage display, Kiosks, ATM, Advertising, ATM, Medical instruments, Military, Commercial transportation, Industrial applications

## Infrared touch screen benefits

### 1. High stability

Changes in the time or environment will not caused any drift.

### 2. High light transmittance

The touch screen has no intermediate touch overlay, enabling light transmittance to reach as high as 100%

### 3. Long service life

Extremely durable, scratch resistant



### 4. Easy activation

Touch pressure is not required; no special material is required is for touch activation.

An activating stylus can be used whether soft or hard -conductor or nonconductor.

### 5. Easy fitting

Enables to fit attractively over the front bezel of the normal displays by overlay solutions.

Product	Features	Size	Remarks
	Mechanical Mounting Type : - A type : Side hole Mounting - B type : Rear hole Mounting	10.4" ~ 103"	Fit in with LCD, PDP, DLP etc... Touch interface : USB and RS232
	The add on range of infrared touch frame are primarily aimed at large sized LCD and PDP, etc... displays and the design enables to fit attractively over the front bezel of the normal Monitor	32" ~ 103"	



Nexio Infrared Touch Screen

# NIB Series

## >> Specification

SIZE(Inch)	Part #	Touch Active Area			Outside Dimensions		
		Width(mm)	Vertical(mm)	Diag(mm)	Width(mm)	Vertical(mm)	Thickness(mm)
10.4	NIB 104 A	208.6	155.8	260.3	303.0	230.0	10.0
10.4	NIB 104 B	208.6	155.8	260.3	283.0	230.0	10.0
12.1	NIB 121 A	243.3	181.8	303.7	329.0	247.5	10.0
12.1	NIB 121 B	243.3	181.8	303.7	309.0	247.5	10.0
15	NIB 150 A	303.6	227.2	379.2	397.5	299.0	10.3
15	NIB 150 B	303.6	227.2	379.2	375.5	299.0	10.3
17	NIB 170 A	336.7	269.3	431.2	425.0	334.0	10.3
17	NIB 170 B	336.7	269.3	431.2	415.0	334.0	10.3
19	NIB 190 A	375.8	300.4	481.2	464.0	365.0	10.3
19	NIB 190 B	375.8	300.4	481.2	440.0	365.0	10.3
22	NIB 220 A	474.0	296.1	558.9	564.0	364.0	11.5
22	NIB 220 B	474.0	296.1	558.9	542.0	364.0	11.5
23	NIB 230 A	507.9	285.4	582.6	602.0	357.0	11.5
23	NIB 230 B	507.9	285.4	582.6	580.0	357.0	11.5
24	NIB 240 A	518.5	324.0	611.4	615.6	394.4	11.5
24	NIB 240 B	518.5	324.0	611.4	591.6	394.4	11.5
26	NIB 260 A	575.3	323.6	660.1	669.0	395.0	12.0
26	NIB 260 B	575.3	323.6	660.1	647.0	395.0	12.0
32	NIB 320 A	700.5	395.6	804.5	809.0	482.0	11.5
32	NIB 320 B	700.5	395.6	804.5	787.0	482.0	11.5
40	NIB 400 A	882.8	495.2	1012.2	988.0	573.0	14.5
40	NIB 400 B	882.8	495.2	1012.2	968.0	573.0	14.5
42	NIB 420 A	928.4	518.0	1063.1	1045.0	615.0	14.5
42	NIB 420 B	928.4	518.0	1063.1	1023.0	615.0	14.5
46	NIB 460 A	1019.6	569.3	1167.8	1127.0	653.0	14.5
46	NIB 460 B	1019.6	569.3	1167.8	1105.0	653.0	14.5
50	NIB 500 A	1105.1	620.6	1267.4	1227.0	721.0	14.5
50	NIB 500 B	1105.1	620.6	1267.4	1205.0	721.0	14.5
52	NIB 520 B	1150.7	649.1	1321.2	1242.0	742.0	14.5
57	NIB 570 B	1253.3	700.4	1435.7	1346.0	795.0	14.5
60	NIB 600 B	1316.0	470.3	1509.9	1425.0	850.0	15.0
63	NIB 630 B	1395.8	785.9	1601.8	1536.0	926.0	50.0
67	NIB 670 B	1481.3	831.5	1698.7	1615.0	966.0	13.6
70	NIB 700 B	1561.1	877.1	1790.6	1692.0	1014.0	10.0
71	NIB 710 B	1561.1	877.1	1790.6	1704.0	1009.0	10.0
73	NIB 730 B	1601.0	894.2	1833.8	1733.0	1027.0	10.0
84	NIB 840 B	1697.9	1270.4	2120.6	1902.0	1475.0	10.0
91	NIB 910 B	2011.4	1127.9	2306.1	2180.0	1300.0	10.0
100	NIB 1000 B	2210.9	1241.9	2535.8	2409.0	1440.0	10.0
103	NIB 1030 B	2262.2	1270.4	2594.5	2420.0	1427.0	25.0

※ Note : The specification are subject to change without prior notice.

Exclusief dealer van Nexio in de BeneLux:

### **NEXIO** NEXIO CO., LTD

Digital Next Generation Display Provider  
<http://www.inexio.co.kr>  
 5F Seong-Woong B/D, 898-3, Jakjun-Dong,  
 Kyeyang-gu, Incheon, Korea  
 Tel : +82 32 556 9545~7  
 Fax : +82 32 556 9544  
 E-mail : sales@inexio.co.kr

By distributor : A1Touch Solution BV  
 Hogeweg 21  
 6367 BA Voerendaal  
 Nederland  
 Tel : 045-5748190  
 Fax : 045-5748191  
 E-mail : info@A1TouchSolution.nl