



**Technical Parameters**

- 0: Interface :USB
- 1: Touch point: 10
- 2: Cover lens + Sensor glass + OCA+PPC
- 3: Cover lens Thickness =3 mm
- 4: Sensor glass Thickness = 0.7 mm
- 5: OCA Thickness = 0.2 mm
- 6: Total Thickness = 3.9 mm
- 7: Sensor Process: Print Process (ITO Pattern) +Laser Ag(Metal line)
- 8: Input Voltage 3.5V~5.5V, Typical 5V
- 9: Transmittance: >85%
- 10: Surface Hardness: >6H
- 11: Operating Conditions : -10 to 70 °C
- 12: Storage Conditions : -20 to 70 °C
- 13: Relative Humidity: 95% at 60°C, RH Non-condensing
- 14: Dimension tolerance: ±0.2mm

Front view

Side view

Back view

|             |    |                      |              |
|-------------|----|----------------------|--------------|
|             |    | Alltouch Solution BV |              |
| Drawing By  | o1 | Materials            | Glass        |
| Checked By  |    | Scale                | 1:1          |
| Approved By |    | Units                | mm           |
| Page 1 of 1 |    | Drawing Name         | 17" (5:4)    |
| Page 1 of 1 |    | Drawing No.          | EG-17-012-V1 |

